

Cod.

FLANGE CIECHE in ACCIAIO

EN 1092-1 tipo 5 pn16

EN 1092-1 tipo 5 pn25

EN 1092-1 tipo 5 pn40

(ex uni 6093 e uni 6094 e uni 6095)

Indicazioni per la design. DN	a mm	b mm	D mm	f mm	N° fori	Filettatura delle viti mm	Peso circa Kg
PN 16							
10	60	14	90	14	4	M 12	0,63
15	65	14	95	14	4	M 12	0,71
20	75	16	105	14	4	M 12	1,01
25	85	16	115	14	4	M 12	1,22
32	100	16	140	18	4	M 16	1,80
40	110	16	150	18	4	M 16	2,09
50	125	18	165	18	4	M 16	2,87
65	145	18	185	18	4	M 16	3,65
80	160	20	200	18	8	M 16	4,61
100	180	20	220	18	8	M 16	5,65
125	210	22	250	18	8	M 16	8,12
150	240	22	285	22	8	M 20	10,5
175	270	24	315	22	8	M 20	14,1
200	295	24	340	22	12	M 20	16,2
250	355	26	405	25	12	M 22	25,1
300	410	28	460	25	12	M 22	35,2
350	470	30	520	25	16	M 22	48,2
400	525	32	580	30	16	M 27	63,5
450	585	40	640	30	20	M 27	77,2
500	650	44	715	33	20	M 30	102
PN 25							
175	280	28	330	25	12	M 22	17,5
200	310	30	360	25	12	M 22	22,6
250	370	32	425	30	12	M 27	33,5
300	430	34	485	30	16	M 27	46,3
350	490	38	555	33	16	M 30	68,1
400	550	40	620	36	16	M 33	89,7
450	600	46	670	36	20	M 33	109
500	660	54	730	36	20	M 33	137
PN 40							
10	60	16	90	14	4	M 12	0,72
15	65	16	95	14	4	M 12	0,81
20	75	18	105	14	4	M 12	1,14
25	85	18	115	14	4	M 12	1,38
32	100	18	140	18	4	M 16	2,03
40	110	18	150	18	4	M 16	2,35
50	125	20	165	18	4	M 16	3,20
65	145	22	185	18	8	M 16	4,29
80	160	24	200	18	8	M 16	5,53
100	190	24	235	22	8	M 20	7,59
125	220	26	270	25	8	M 22	10,8
150	250	28	300	25	8	M 22	14,7
175	295	32	350	30	12	M 27	22,0
200	320	34	375	30	12	M 27	27,2
250	385	38	450	33	12	M 30	44,4
300	450	42	515	33	16	M 30	64,2
350	510	46	580	36	16	M 33	89,5
400	585	50	660	39	16	M 36 x 3	127
450	610	57	685	39	20	M 36 x 3	141
500	670	57	755	42	20	M 39 x 3	172