



**RIDUZIONI CONCENTRICHE ed EC-CENTRICHE**

SS asme B16.9 ASTM A-403  
AISI 304/304L - 316/316L

De in pollici	De in mm		SPESSORI						RIDUZ. Altezza	L	M
			Sch. 10 S		Sch. 40 S Standard		Sch. 80 S Extra Strong				
			mm		mm		mm				
D	d	S	S1	S	S1	S	S1	H			
3/4 x 1/2	26,7	21,3	2,11	2,11	2,87	2,77	3,91	3,73	38		
1 x 1/2 1 x 3/4	33,4	21,3 26,7	2,77	2,11 2,11	3,38	2,77 2,87	4,55	3,73 3,91	51		
1 1/4 x 1/2 1 1/4 x 3/4 1 1/4 x 1	42,2	21,3 26,7 33,4	2,77	2,11 2,11 2,77	3,56	2,77 2,87 3,38	4,85	3,73 3,91 4,55	51		
1 1/2 x 1/2 1 1/2 x 3/4 1 1/2 x 1 1 1/2 x 1 1/4	48,3	21,3 26,7 33,4 42,2	2,77	2,11 2,11 2,77 2,77	3,68	2,77 2,87 3,38 3,56	5,08	3,73 3,91 4,55 4,85	64		
2 x 1/2 2 x 3/4 2 x 1 2 x 1 1/4 2 x 1 1/2	60,3	21,3 26,7 33,4 42,2 48,3	2,77	2,11 2,11 2,77 2,77	3,91	2,77 2,87 3,38 3,56 3,68	5,54	3,73 3,91 4,55 4,85 5,08	76		
2 1/2 x 1 2 1/2 x 1 1/4 2 1/2 x 1 1/2 2 1/2 x 2	73,0	33,4 42,2 48,3 60,3	3,05	2,77 2,77 2,77 2,77	5,16	3,38 3,56 3,68 3,91	7,01	4,55 4,85 5,08 5,54	89		